	Resimix s.r.l.	Revision nr. 3
	F302 - RESIMALTA 202 W Comp. A	Dated 04/01/2017 Printed on 04/01/2017 Page n. 1/14

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking.

#### 1.1. Product identifier.

Code: F302  
Product name: RESIMALTA 202 W Comp. A  
Chemical name and synonym: Reaction product: bisphenol-A-(epichlorhydrin)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use. Epoxy mortar

Identified Uses	Industrial.	Professional.	Consumer.
Epoxy mortar	✔	✔	-

#### 1.3. Details of the supplier of the safety data sheet.

Name: Resimix s.r.l.  
Full address: via Pacinotti 12/14  
District and Country: 36040 Brendola (VI)  
Italia  
Tel. +39 (0) 444 400 773  
Fax. +39 (0) 444 601 662  
e-mail address of the competent person.  
responsible for the Safety Data Sheet. laboratorio@resimix.com  
Product distribution by: Resimix s.r.l.

#### 1.4. Emergency telephone number.

For urgent inquiries refer to.

CAVp Osp. Pediatrico Bambino Gesù, Roma 06 68593726  
Az. Osp. Univ. Foggia, Foggia 0881-732326  
Az. Osp. "A. Cardarelli", Napoli 081-7472870  
CAV Policlinico "Umberto I", Roma 06-49978000  
CAV Policlinico "A. Gemelli", Roma 06-3054343  
Az. Osp. "Careggi" U.O. Tossicologia Medica, Firenze 055-7947819  
CAV Centro Nazionale di Informazione Tossicologica, Pavia 0382-24444  
Osp. Niguarda Ca" Granda, Milano 02-66101029  
Azienda Ospedaliera Papa Giovanni XXII, Bergamo 80088330


### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

#### Hazard classification and indication:

Germ cell mutagenicity, category 2	H341	Suspected of causing genetic defects.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 2/14

## 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Hazard statements:

<b>H341</b>	Suspected of causing genetic defects.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH205</b>	Contains epoxy constituents. May produce an allergic reaction.

Precautionary statements:

<b>P201</b>	Obtain special instructions before use.
<b>P273</b>	Avoid release to the environment.
<b>P280</b>	Wear protective gloves / clothing and eye / face protection.
<b>P302+P352</b>	IF ON SKIN: Wash with plenty of water
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P333+P313</b>	If skin irritation or rash occurs: Get medical advice / attention.
<b>P501</b>	Dispose of contents / container in accordance with local / regional / national / international.

**Contains:** 2,3-epoxypropyl o-tolyl ether  
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).

## 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.


## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

	Resimix s.r.l.	Revision nr. 3
	F302 - RESIMALTA 202 W Comp. A	Dated 04/01/2017 Printed on 04/01/2017 Page n. 3/14

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### Identification.

**Classification 1272/2008 (CLP).**

#### INERT

CAS. -  $50 \leq x < 100$

EC. -

INDEX. -

**Reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).**

CAS. 25068-38-6  $10 \leq x < 30$  Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411

EC. 500-033-5

INDEX. 603-074-00-8

Reg. no. 01-2119456619-26

#### 2,3-epoxypropyl o-tolyl ether

CAS. 2210-79-9  $1 \leq x < 10$  Muta. 2 H341, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411, Note c

EC. 218-645-3

INDEX. 603-056-00-X

Reg. no. 01-2119966907-18

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed.


Specific information on symptoms and effects caused by the product are unknown.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 4/14

### 5.1. Extinguishing media.

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture.

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.


Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

	Resimix s.r.l.	Revision nr. 3
	F302 - RESIMALTA 202 W Comp. A	Dated 04/01/2017 Printed on 04/01/2017 Page n. 5/14

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

#### Reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700).

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,006	mg/l
Normal value in marine water	0,001	mg/l
Normal value for fresh water sediment	0,996	mg/kg
Normal value for marine water sediment	0,1	mg/kg
Normal value for water, intermittent release	0,018	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the food chain (secondary poisoning)	11	mg/kg
Normal value for the terrestrial compartment	0,196	mg/kg

#### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	VND	0,75 mg/kg bw/d	VND	0,75 mg/kg bw/d				
Inhalation.					VND	12,25 mg/m3	VND	12,25 mg/m3
Skin.	VND	3,571 mg/kg bw/d	VND	3,571 mg/kg bw/d	VND	8,33 mg/kg bw/d	VND	8,33 mg/kg bw/d


#### 2,3-epoxypropyl o-tolyl ether

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,0028	mg/l
Normal value in marine water	0,00028	mg/l
Normal value for fresh water sediment	0,039	mg/kg
Normal value for marine water sediment	0,004	mg/kg
Normal value for water, intermittent release	0,028	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,012	mg/kg

#### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers. Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	0,14 mg/kg bw/d				

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 6/14

Inhalation.	40 mg/m3	40 mg/m3	0,46 mg/m3	0,46 mg/m3
Skin.			VND	0,139 mg/kg bw/d

## 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.


**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700).**

Material of gloves for long term application (BTT > 480 min): ethyl vinyl alcohol laminate (EVAL), butyl rubber.

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	viscous liquid
Colour	brown
Odour	mild
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 60 °C.
Evaporation Rate	Not available.

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 7/14

Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,95
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

## 9.2. Other information.

VOC (Directive 2010/75/EC) :	0
VOC (volatile carbon) :	0

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

The product may react exothermically on contact with strong oxidising or reducing agents, strong acids or bases.

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
No data available about the reactivity on the product itself.

2,3-epoxypropyl o-tolyl ether  
No data available about the reactivity on the product itself.

### 10.2. Chemical stability.


Excessively high temperatures can cause thermal decomposition.

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
Stable in normal conditions of use and storage.

2,3-epoxypropyl o-tolyl ether  
Stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

See paragraph 10.1.

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 8/14

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
By weight over 0,5 kg to add an aminic base substance drives to a strong exothermic reaction.  
The reaction with aminic components is not reversible .

2,3-epoxypropyl o-tolyl ether  
Stable in normal conditions of use and storage.

#### 10.4. Conditions to avoid.

Avoid overheating.

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
Avoid exposure to: high temperatures.  
The thermal decomposition develops gases which can cause pressure in closed systems.

2,3-epoxypropyl o-tolyl ether  
Avoid contact with: strong acids, strong bases, strong oxidising agents.  
Avoid exposure to: heat.

#### 10.5. Incompatible materials.

Oxidising or reducing agents. Strong acids or bases.

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
Avoid contact with: oxidising agents, acids, bases. Avoid unintended contact with amines.

2,3-epoxypropyl o-tolyl ether  
Avoid contact with: acids, bases, oxidising agents.

#### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.


Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
The thermal decomposition develops: carbon monoxide, water, phenols, phenolic derivatives  
An uncontrolled exothermic reaction build up phenolic derivatives , carbon monoxide and water.

2,3-epoxypropyl o-tolyl ether  
In decomposition develops: carbon oxides, toxic fumes.

## SECTION 11. Toxicological information.

#### 11.1. Information on toxicological effects.



	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 9/14

#### ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component).  
LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component).  
LD50 (Oral) of the mixture: Not classified (no significant component).  
LD50 (Dermal) of the mixture: Not classified (no significant component).

2,3-epoxypropyl o-tolyl ether  
LD50 (Oral).> 5000 mg/kg male/female rat  
LD50 (Dermal).> 2000 mg/kg male/female rat  
LC50 (Inhalation).> 6,1 ppm/4h male/female rat

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700).  
LD50 (Oral).> 2000 mg/kg female rat  
LD50 (Dermal).> 2000 mg/kg male/female rat

#### SKIN CORROSION / IRRITATION.

Causes skin irritation.

#### SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye irritation.

#### RESPIRATORY OR SKIN SENSITISATION.

Sensitising for the skin.

#### GERM CELL MUTAGENICITY.

Suspected of causing genetic defects.

#### CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

#### REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

#### STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

#### STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

#### ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

### SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on aquatic environment.

#### 12.1. Toxicity.

2,3-epoxypropyl o-tolyl ether

LC50 - for Fish. > 2,8 mg/l/96h *Salmo gairdneri*

EC50 - for Crustacea. 3,3 mg/l/48h *Daphnia magna*

EC50 - for Algae / Aquatic Plants. 5,1 mg/l/72h *Pseudokirchnerella subcapitata*

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700).


LC50 - for Fish. 3,6 mg/l/96h *Salmo gairdneri*

EC50 - for Crustacea. 1,7 mg/l/48h *Daphnia magna*

EC50 - for Algae / Aquatic Plants. 9,4 mg/l/72h *Scenedesmus capricornutum*

Chronic NOEC for Crustacea. 0,3 mg/l *Daphnia magna*

#### 12.2. Persistence and degradability.

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 10/14

2,3-epoxypropyl o-tolyl ether  
Solubility in water. moderately soluble 840 mg/l  
NOT rapidly biodegradable. 11 a 17 % 28 d

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
Solubility in water. slightly soluble > 5,4 - < 8,4 mg/l  
NOT rapidly biodegradable. 5 % 28 d

### 12.3. Bioaccumulative potential.

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
BCF. 31

### 12.4. Mobility in soil.

2,3-epoxypropyl o-tolyl ether  
Partition coefficient: soil/water. 2,32

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ).  
Partition coefficient: soil/water. 2,65

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.


### 12.6. Other adverse effects.

Information not available.

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.  
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 11/14

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number.

Not applicable.

#### 14.2. UN proper shipping name.

Not applicable.

#### 14.3. Transport hazard class(es).

Not applicable.

#### 14.4. Packing group.

Not applicable.

#### 14.5. Environmental hazards.


Not applicable.

#### 14.6. Special precautions for user.

Not applicable.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 12/14

## SECTION 15. Regulatory information.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC:

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 3

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.


### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Muta. 2</b>	Germ cell mutagenicity, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3

	Resimix s.r.l.	Revision nr. 3
	<b>F302 - RESIMALTA 202 W Comp. A</b>	Dated 04/01/2017 Printed on 04/01/2017 Page n. 13/14

<b>H341</b>	Suspected of causing genetic defects.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH205</b>	Contains epoxy constituents. May produce an allergic reaction.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY


1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety

	<b>Resimix s.r.l.</b>	Revision nr. 3  Dated 04/01/2017 Printed on 04/01/2017 Page n. 14/14
	<b>F302 - RESIMALTA 202 W Comp. A</b>	

laws and regulations. The producer is relieved from any liability arising from improper uses.  
Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: all sections revised according to Regulation 830/2015/EC.