



**RESIMIX s.r.l.**  
Via A. Pacinotti, 12/14 - 36040 BRENDOLA (VI)  
Tel. 0444-400773 r.a. - telefax 0444-601662  
[www.resimix.com](http://www.resimix.com) - email: [info@resimix.com](mailto:info@resimix.com)



**DECLARATION OF PERFORMANCE**  
(in accordance with Regulation UE CPR N. 305/2011)

**N° DoP\_5506\_RM205\_EN\_002**

1. Unique identification code of the product-type:  
**RESIMALTA 205.**
2. Number of type, batch of serial number or other element allowing the identification of the construction product in accordance with art. 11, par. 4:  
**Date and manufacturing plant are printed on the packaging or on the transport document.**
3. Intended use of the construction product, in accordance with the relevant harmonized technical specification as provided by the manufacturer:  
**Structural and non structural repair products for concrete.**
4. Name and address of the manufacturer:  
**RE.SI.MIX S.r.l.**  
**via Pacinotti, 12/14**  
**36040, Brendola (VI)**  
**tel: 0444 400773**  
**fax: 0444 601662**  
**e-mail: [info@resimix.com](mailto:info@resimix.com)**
5. If appropriate, the name and address of the representative whose mandate covers the tasks of art. 12, par. 2:  
**Not applicable.**
6. System of assessment and verification of constancy of performance of construction product (AVCP):  
**2+; 4 for reaction to fire.**
7. Harmonised standard:  
**UNI EN 1504-3.**
8. The notified body:  
**ICMQ S.p.A., identification number 1305,**  
**issued the Certificate of Factory Production Control No. 1305-CPR-1070.**
9. In the case of a declaration of performance concerning a construction product for which it has been granted a European Technical Assessment:  
**Not applicable.**
10. Declared performance:

Compressive strength:	Class R4.	EN 1504-3
Chloride ion content:	NPD.	
Adhesive bond:	≥ 1.5 MPa.	
Restrained shrinkage/expansion:	NPD.	
Carbonation resistance:	NPD.	
Elastic modulus:	24.108 GPa.	
Thermal compatibility part 1:	≥ 1.5 Mpa.	
Skid resistance:	NPD.	
Coefficient of thermal expansion:	NPD.	
Capillary absorption:	≤ 0.5 kg·m <sup>-2</sup> ·h <sup>-0.5</sup> .	
Reaction to fire:	F.	
Dangerous substances:	NPD.	

11. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Brendola, february 4<sup>th</sup>, 2015

Signed in the name and on behalf of the manufacturer  
Mr. Mattia Milano, technical development office