

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 1 / 10 ΕN

F427 - REPIKIT VE 40 Comp. A

Safety data sheet SECTION 1. Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier F427 Code: **REPIKIT VE 40 Comp. A** Product name Chemical name and synonym Unsaturated polyester resin 1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use Chemical anchor based on polyester resin Professional **Identified Uses** Industrial Consumer Chemical anchor based on polyester resin 1.3. Details of the supplier of the safety data sheet Name Resimix s.r.l. Full address via Pacinotti 12/14 District and Country 36040 Brendola (VI) Italia +39 (0) 444 400 773 Tel. Fax +39 (0) 444 601 662 e-mail address of the competent person responsible for the Safety Data Sheet laboratorio@resimix.com Product distribution by: Resimix s.r.l. 1.4. Emergency telephone number For urgent inquiries refer to CAVp Osp. Pediatrico Bambino Gesù, Roma 06 68593726 Az. Osp. Univ. Foggia, Foggia 0881-732326 Az. Osp. "A. Cardarelli", Napoli 081-7472870 CAV Policlinico "Umberto I", Roma 06-49978000 CAV Policlinico "A. Gemelli", Roma 06-3054343 Az. Osp. "Careggi" U.O. Tossicologia Medica, Firenze 055-7947819 CAV Centro Nazionale di Informazione Tossicologica, Pavia 0382-24444 Osp. Niguarda Ca" Granda, Milano 02-66101029 Azienda Ospedaliera Papa Giovanni XXII, Bergamo 80088330 **SECTION 2. Hazards identification** 2.1. Classification of the substance or mixture The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet. Hazard classification and indication

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 2 / 10 ΕN

F427 - REPIKIT VE 40 Comp. A

SECTION 2. Hazards identification ... / >>

Signal words: Warning

elgilar nerder	
Hazard statements:	
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
Precautionary statement	S
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves / eye protection / face protection.
P302+P352	IF ON SKIN: Wash with plenty of water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
	Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice / attention.
P337+P313	If eye irritation persists: Get medical advice / attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: use appropriate means to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents / container in accordance with local / regional / national / international.
Contains:	VinyItoluene

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

Vinyltoluene

CAS 25013-15-4 $10 \le x < 20$ EC 246-562-2 INDEX Reg. no. 01-2119622074-50

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

Flam. Liq. 3 H226, Acute Tox. 4 H332, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available



Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 3 / 10

F427 - REPIKIT VE 40 Comp. A

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available



F427 - REPIKIT VE 40 Comp. A

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 4 / 10

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

AUS	Österreich	Grenzwerteverordnung 2011 - GKV 2011
BEL	Belgique	AR du 11/3/2002. La liste est mise à jour pour 2010
CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail 2014. / Grenzwerte am Arbeitsplatz
DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits

				Viny	ltoluene				
Threshold Limit Valu	le								
Туре С	Country	TWA/8h		STEL/15	min				
		mg/m3	ppm	mg/m3	ppm				
MAK A	AUS	480	100	480	100				
VLEP E	BEL	246	50	490	100				
MAK C	CHE	240	50	480	100				
AGW E	DEU	490	100	980	200				
VLA E	ESP	246	50	492	100				
VLEP F	RA	240	50						
WEL C	GBR	491	100	736	150				
Predicted no-effect of	concentrati	on - PNEC							
Normal value in fre	esh water						0,05	mg/l	
Normal value in ma	arine water						0,002	mg/l	
Normal value for fr	esh water s	ediment					0,684	mg/kg	
Normal value for m	narine water	r sediment					0,068	mg/kg	
Normal value for w	ater, interm	ittent relea	se				0,013	mg/l	
Normal value of S	TP microorg	janisms					1	mg/l	
Normal value for the	ne food chai	in (seconda	ry poisoning)			2,5	mg/kg	
Normal value for the	ne terrestria	I compartm	ent				0,133	mg/kg	
Health - Derived no-	effect level	- DNEL / D	MEL						
	Effects	s on consur	ners			Effects on wo	orkers		
Route of exposure	Acute	local Acut	е	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
		syste	emic	local	systemic		systemic	local	systemic
Inhalation								37 mg/m3	37 mg/m3

Vinultaluana

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.



F427 - REPIKIT VE 40 Comp. A

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 5 / 10

SECTION 8. Exposure controls/personal protection/>>

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour Odour Odour threshold pH Melting point / freezing point Initial boiling point Boiling range Flash point Evaporation Rate Flammability of solids and gases Lower inflammability limit Upper inflammability limit Lower explosive limit Upper explosive limit Upper explosive limit Vapour pressure Vapour density Relative density Solubility Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature Viscosity Explosive properties	>	pasty liquid beige aromatic Not available Not available Not available 165 °C Not available 53 °C Not available S3 °C Not available Not available Not available Not available Not available 6 hPa a 20°C Not available 1,70 insoluble in water Not available Not available Not available Not available Not available Not available Not available Not available Not available
Oxidising properties		Not available

VOC (Directive 2010/75/EC) :	15,00 %	-	255,00	g/litre
VOC (volatile carbon):	13,71 %	-	233,03	g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

The product reacts with hydroperoxide / organic peroxides.

10.6. Hazardous decomposition products



F427 - REPIKIT VE 40 Comp. A

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 6 / 10

SECTION 10. Stability and reactivity ... / >>

The thermal decomposition develops: carbon oxides.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: LD50 (Oral) of the mixture: LD50 (Dermal) of the mixture:

> Vinyltoluene LD50 (Oral) LD50 (Dermal)

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

> 20 mg/l Not classified (no significant component) Not classified (no significant component)

4000 mg/kg male rat > 4,45 mg/kg male/female rabbit



F427 - REPIKIT VE 40 Comp. A

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 7 / 10 ΕN

SECTION 12. Ecological information

12.1. Toxicity

Vinyltoluene LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish Chronic NOEC for Crustacea

2,8 mg/l/96h Lepomis macrochirus 1,3 mg/l/48h Daphnia magna 2,6 mg/l/72h Pseudokirchnerella subcapitata 1,636 mg/l 0,498 mg/l Daphnia magna

12.2. Persistence and degradability

Vinyltoluene Solubility in water NOT rapidly degradable

89 mg/l

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1866

14.2. UN proper shipping name

ADR / RID:	RESIN SOLUTION (vinyltoluene)
IMDG:	RESIN SOLUTION (vinyltoluene)
IATA:	RESIN SOLUTION (vinyltoluene)

@EPY 9.4.5 - SDS 1004.4

RESIMIX

Resimix s.r.l. F427 - REPIKIT VE 40 Comp. A

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 8 / 10

SECTION 14. Transport information ... / >>

14.3	Transport	hazard	class	(es)

ADR / RID:	Class: 3	Label: 3
IMDG:	Class: 3	Label: 3
IATA:	Class: 3	Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: 111

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E
	Special Provision: -		
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special Instructions:	A3	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 **Product** Point

P5c

3 - 40

Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH) None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention: None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment



F427 - REPIKIT VE 40 Comp. A

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 9 / 10

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation
H319	Causes serious eye irritation.
H315	Causes skin irritation.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website



Resimix s.r.l. F427 - REPIKIT VE 40 Comp. A

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 10 / 10

SECTION 16. Other information ... / >>

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.