

# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 1 / 10

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: FB180

Product name REPIKIT VE 40 Comp. B
Chemical name and synonym Dibenzoyl peroxide

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Polyester resin catalyst

Identified Uses	Industrial	Professional	Consumer
Polyester resin catalyst	<b>✓</b>	-	-
1.3. Details of the supplier of the safety data she	et		
Name Full address	Resimix s.r.l. via Pacinotti 12/14		
District and Country	36040 Brendola Italia		(VI)
	Tel. +39 (0) 444 400 7	73	

+39 (0) 444 601 662

e-mail address of the competent person responsible for the Safety Data Sheet

eet laboratorio@resimix.com

Fax

Product distribution by: Resimix s.r.l.

## 1.4. Emergency telephone number

For urgent inquiries refer to CAVp Osp. Pediatrico Bambino Gesù, Roma 06 68593726

Az. Osp. Univ. Foggia, Foggia 0881-732326 Az. Osp. "A. Cardarelli", Napoli 081-7472870 CAV Policlinico "Umberto I", Roma 06-49978000 CAV Policlinico "A. Gemelli", Roma 06-3054343

Az. Osp. "Careggi" U.O. Tossicologia Medica, Firenze 055-7947819 CAV Centro Nazionale di Informazione Tossicologica, Pavia 0382-24444

Osp. Niguarda Ca" Granda, Milano 02-66101029

Azienda Ospedaliera Papa Giovanni XXII, Bergamo 80088330

# **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2

Skin sensitization, category 1

Hazardous to the aquatic environment, acute toxicity, category 1

Hazardous to the aquatic environment, chronic toxicity, category 3

Hazardous to the aquatic environment, chronic toxicity, category 3

Hazardous to the aquatic environment, chronic toxicity, category 3

Hazardous to the aquatic environment, chronic toxicity, category 3

Hazardous to the aquatic environment, chronic toxicity, category 3

Hazardous to the aquatic environment, chronic toxicity, category 3

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 2 / 10

#### SECTION 2. Hazards identification .../>>

Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.H317 May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

**H412** Harmful to aquatic life with long lasting effects.

Precautionary statements:

**P273** Avoid release to the environment.

**P280** Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P337+P313 If eye irritation persists: Get medical advice / attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents / container in accordance with local / regional / national / international.

Contains: Dibenzoyl peroxide

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## **SECTION 3. Composition/information on ingredients**

### 3.1. Substances

Information not relevant

### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

Dibenzoyl peroxide

CAS 94-36-0 10 ≤ x < 15 Org. Perox B H241, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10,

Aquatic Chronic 1 H410 M=10

EC 202-327-6 INDEX 617-008-00-0 Reg. no. 01-2119511472-50

Nonylbenzoate, branched and linear

CAS  $670241-72-2 \ 5 \le x < 10$  Aquatic Chronic 2 H411

EC 447-010-5

INDEX

Reg. no. 01-0000018876-55

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures**

# 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.



# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 3 / 10

#### SECTION 4. First aid measures .../>>

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6. Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.



# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 4 / 10

### SECTION 7. Handling and storage .../>>

7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

### 8.1. Control parameters

Regulatory References:

AUS Österreich Grenzwerteverordnung 2011 - GKV 2011

BEL Belgique AR du 11/3/2002. La liste est mise à jour pour 2010

CHE Suisse / Schweiz Valeurs limites d'exposition aux postes de travail 2014. / Grenzwerte am Arbeitsplatz

DEU Deutschland MAK-und BAT-Werte-Liste 2012

ESP España INSHT - Límites de exposición profesional para agentes químicos en España 2015

FRA France JORF n°0109 du 10 mai 2012 page 8773 texte n° 102

GBR United Kingdom EH40/2005 Workplace exposure limits

				Dibenzo	yl peroxide				
hreshold Limit Valu	е				,				
Type C	ountry	TWA/8h		STEL/15r	min				
• •	-	mg/m3	ppm	mg/m3	ppm				
MAK A	US	5		10		INHAL			
VLEP B	EL	5							
MAK C	HE	5		5		INHAL			
AGW D	EU	5		5		INHAL			
VLA E	SP	5							
VLEP F	RA	5							
WEL G	BR	5							
Predicted no-effect c	oncentra	ation - PNE	С						
Normal value in fre	sh water						0,00002	mg/l	
Normal value in marine water 0,00000							0,000002	mg/l	
Normal value for fresh water sediment							0,013	mg/kg	
Normal value for marine water sediment						0,001	mg/kg		
Normal value for water, intermittent release						0,000602	mg/l		
Normal value of STP microorganisms							0,35	mg/l	
Normal value for th	e terrestr	rial compar	tment				0,003	mg/kg	
lealth - Derived no-e	ffect lev	el - DNEL	DMEL						
	Effe	cts on cons	umers			Effects on workers			
Route of exposure	Acu	te local Ad	cute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
		sy	stemic	local	systemic		systemic	local	systemic
Oral				VND	2				
					mg/kg bw/d				
Inhalation								VND	39 mg/m3
Skin								0,034	13,3
								mg/cm	mg/kg
								2	bw/d

#### Legend

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction. VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.



# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 5 / 10

## SECTION 8. Exposure controls/personal protection ..../>>

**EYE PROTECTION** 

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. **ENVIRONMENTAL EXPOSURE CONTROLS** 

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance liquid Colour black characteristic Odour Odour threshold Not available Not available Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available Flash point 60 **Evaporation Rate** Not available Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available 1,50 Relative density Not available Not available

Solubility Partition coefficient: n-octanol/water Auto-ignition temperature Not available Decomposition temperature > 50°C

> 60 St (ISO 2431) Viscosity Explosive properties Not available Not available Oxidising properties

## 9.2. Other information

VOC (Directive 2010/75/EC): 0 VOC (volatile carbon): 0

# SECTION 10. Stability and reactivity

### 10.1. Reactivity

Information not available

#### 10.2. Chemical stability

The product is stable if stored in original containers at temperatures lower than the self accelerated decomposition temperature (SADT).

## 10.3. Possibility of hazardous reactions

Information not available

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition. Avoid transferring into containers that may have been contaminated with other substances. Avoid storing close to inflammable or combustible products.



# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 6 / 10

## SECTION 10. Stability and reactivity .../>>

Avoid contact with amines, strong reducing agents, acids and alkalis.

### 10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

#### 10.6. Hazardous decomposition products

Thermal decomposition can lead to the formation of explosive peroxides or other potentially hazardous substances.

The thermal decomposition develops carbon oxides.

# **SECTION 11. Toxicological information**

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

### **ACUTE TOXICITY**

LC50 (Inhalation) of the mixture:

LD50 (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

## RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

### **GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

#### **CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

# **STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

### **STOT - REPEATED EXPOSURE**



# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 7 / 10

### SECTION 11. Toxicological information .../>>

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD** 

Does not meet the classification criteria for this hazard class

# **SECTION 12. Ecological information**

This product is dangerous for the environment and highly toxic for aquatic organisms.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

0,06 mg/l/96h Oncorhynchus mykiss

#### 12.1. Toxicity

Dibenzoyl peroxide

LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants

0,11 mg/l/48h Daphnia magna 0,071 mg/l/72h Pseudokirchnerella subcapitata

Nonylbenzoate, branched and linear

EC50 - for Crustacea Chronic NOEC for Fish > 2,2 mg/l/48h Daphnia magna > 1,23 mg/l Cyprinus carpio

slightly soluble 0,35 mg/l

#### 12.2. Persistence and degradability

Dibenzoyl peroxide

Solubility in water

Rapidly degradable 71 % 28 d

### 12.3. Bioaccumulative potential

Information not available

### 12.4. Mobility in soil

Dibenzoyl peroxide

Partition coefficient: soil/water 3,8

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING** 

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information**



# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 8 / 10

## SECTION 14. Transport information .../>>

#### 14.1. UN number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not

submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or

5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to

IATA dangerous goods regulations.

### 14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dibenzoyl peroxide; benzoic acid,nonyl ester,

branched and linear)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dibenzoyl peroxide; benzoic acid,nonyl ester,

branched and linear)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dibenzoyl peroxide; benzoic acid,nonyl ester,

branched and linear)

### 14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9

IMDG: Class: 9 Label: 9

IATA: Class: 9 Label: 9



#### 14.4. Packing group

ADR / RID, IMDG, IATA: III

#### 14.5. Environmental hazards

ADR / RID: Environmentally Hazardous

IMDG: Marine Pollutant

IATA: Environmentally Hazardous



#### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 90 Limited Quantities: 5 L Tunnel restriction code: (E)

Special Provision: -

IMDG: EMS: F-A, S-F Limited Quantities: 5 L IATA: Cargo: Maximum quantity: 450 L

Cargo: Maximum quantity: 450 L Packaging instructions: 964
Pass.: Maximum quantity: 450 L Packaging instructions: 964

Special Instructions: A97, A158, A197

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

#### ΕN



# Resimix s.r.l.

# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 9 / 10

# **SECTION 15. Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

F1

**Product** 

Point 3

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

#### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Org. Perox B Organic peroxide, category B
Eye Irrit. 2 Eye irritation, category 2
Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H241 Heating may cause a fire or explosion.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP



# FB180 - REPIKIT VE 40 Comp. B

Revision nr.3 Dated 04/07/2017 Printed on 04/07/2017 Page n. 10 / 10

#### SECTION 16. Other information .../>>

- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.