

**FB159 - REPIKIT 310 Comp. B**

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking.

**1.1. Product identifier.**

Code: **FB159**  
Product name: **REPIKIT 310 Comp. B**  
Chemical name and synonym: **pentacthylenehexamine**

**1.2. Relevant identified uses of the substance or mixture and uses advised against.**

Intended use: **Amine hardener for epoxy resin**

Identified Uses	Industrial.	Professional.	Consumer.
Hardener for epoxy resin	✓	✓	-

**1.3. Details of the supplier of the safety data sheet.**

Name: **Resimix s.r.l.**  
Full address: **via Pacinotti 12/14**  
District and Country: **36040 Brendola (VI)**  
**Italia**  
**Tel. +39 (0) 444 400 773**  
**Fax. +39 (0) 444 601 662**

e-mail address of the competent person.  
responsible for the Safety Data Sheet: **laboratorio@resimix.com**  
Product distribution by: **Resimix s.r.l.**

**1.4. Emergency telephone number.**

For urgent inquiries refer to.

**CAVp Osp. Pediatrico Bambino Gesù, Roma 06 68593726**  
**Az. Osp. Univ. Foggia, Foggia 0881-732326**  
**Az. Osp. "A. Cardarelli", Napoli 081-7472870**  
**CAV Policlinico "Umberto I", Roma 06-49978000**  
**CAV Policlinico "A. Gemelli", Roma 06-3054343**  
**Az. Osp. "Careggi" U.O. Tossicologia Medica, Firenze 055-7947819**  
**CAV Centro Nazionale di Informazione Tossicologica, Pavia 0382-24444**  
**Osp. Niguarda Ca" Granda, Milano 02-66101029**  
**Azienda Ospedaliera Papa Giovanni XXII, Bergamo 80088330**

### SECTION 2. Hazards identification.

**2.1. Classification of the substance or mixture.**

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

## Hazard classification and indication:

Acute toxicity, category 4	H302	Harmful if swallowed.
Acute toxicity, category 4	H312	Harmful in contact with skin.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

**FB159 - REPIKIT 310 Comp. B**

Hazardous to the aquatic environment, acute toxicity, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, chronic toxicity, category 1	H410	Very toxic to aquatic life with long lasting effects.

**2.2. Label elements.**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:                      Danger

Hazard statements:

<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H317</b>	May cause an allergic skin reaction.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.

Precautionary statements:

<b>P201</b>	Obtain special instructions before use.
<b>P264</b>	Wash with plenty of water thoroughly after handling.
<b>P272</b>	Contaminated work clothing should not be allowed out of the workplace.
<b>P273</b>	Avoid release to the environment.
<b>P280</b>	Wear protective gloves / clothing and eye / face protection.
<b>P301+P312</b>	IF SWALLOWED: Call a POISON CENTER / doctor if you feel unwell.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
<b>P304+P340</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P310</b>	Immediately call a POISON CENTER / doctor
<b>P501</b>	Dispose of contents / container in accordance with local / regional / national / international.

**Contains:**                      Pentactylenhexamine  
Benzyl alcohol

**2.3. Other hazards.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients.****3.1. Substances.**

Information not relevant.

**FB159 - REPIKIT 310 Comp. B****3.2. Mixtures.**

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**Identification.****Pentathylenehexamine**

CAS. 4067-16-7

50 ≤ x &lt; 100

**Classification 1272/2008 (CLP).**

Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC. 223-775-9

INDEX. 612-064-00-2

Reg. no. 01-2119485826-22

**Benzyl alcohol**

CAS. 100-51-6

10 ≤ x &lt; 30

Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319

EC. 202-859-9

INDEX. 603-057-00-5

Reg. no. 01-2119492630-38

**SECTION 4. First aid measures.****4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed.**

Specific information on symptoms and effects caused by the product are unknown.

For symptoms and effects caused by the contained substances, see chap. 11.

**4.3. Indication of any immediate medical attention and special treatment needed.**

Information not available.

**SECTION 5. Firefighting measures.****5.1. Extinguishing media.**

**SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture.****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

**5.3. Advice for firefighters.****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures.****6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions.**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up.**

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections.**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage.**

### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

FIN	Suomi	HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveysministeriön julkaisuja 2012:5
LVA	Latvija	Ķīmisko vielu aroda ekspozīcijas robežvērtības (AER) darba vides gaisā 2012

### Pentachylenehexamine

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,0025	mg/l
Normal value in marine water	0,0025	mg/l
Normal value for fresh water sediment	0,22	mg/kg
Normal value for marine water sediment	0,14	mg/kg
Normal value for water, intermittent release	0,025	mg/l
Normal value of STP microorganisms	1,64	mg/l
Normal value for the food chain (secondary poisoning)	0,29	mg/kg
Normal value for the terrestrial compartment	0,18	mg/kg

### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	VND	32 mg/kg bw/d	VND	0.65 mg/kg bw/d				
Inhalation.	VND	2542 mg/m3	VND	0.46 mg/m3	VND	8550 mg/m3	VND	1.59 mg/m3
Skin.	1.59 mg/cm2	13 mg/kg bw/d	0.68 mg/cm2	0.4 mg/kg bw/d			0.044 mg/cm2	0.91 mg/kg bw/d

### Benzyl alcohol

#### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
HTP	FIN	45	10		
RV	LVA	5			



## FB159 - REPIKIT 310 Comp. B

## Predicted no-effect concentration - PNEC.

Normal value in fresh water	1	mg/l
Normal value in marine water	0,1	mg/l
Normal value for fresh water sediment	5,27	mg/kg
Normal value for marine water sediment	0,527	mg/kg
Normal value for water, intermittent release	2,3	mg/l
Normal value of STP microorganisms	39	mg/l
Normal value for the terrestrial compartment	0,456	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	VND	20 mg/kg bw/d	VND	4 mg/kg bw/d				
Inhalation.	VND	27 mg/m3	VND	5,4 mg/m3	VND	110 mg/m3	VND	22 mg/m3
Skin.	VND	20 mg/kg bw/d	VND	4 mg/kg bw/d	VND	40 mg/kg bw/d	VND	8 mg/kg bw/d

## Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

## 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

## HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

## SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

## EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

## RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

## ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	black
Odour	amine
Odour threshold.	Not available.
pH.	12,3
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 60 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,050
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	160 - 190 cP (Brookfield, 20°C)
Explosive properties	Not available.
Oxidising properties	Not available.

### 9.2. Other information.

VOC (Directive 2010/75/EC) :	0
VOC (volatile carbon) :	0

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

Pentachylenhexamine  
no data available about the reactivity on the product itself.

Benzyl alcohol  
with strong heating build up explosive mixtures with air.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

Pentactylenhexamine

Stable in normal conditions of use and storage.

Benzyl alcohol

Stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

Pentactylenhexamine

Stable in normal conditions of use and storage.

Benzyl alcohol

Risk of explosion on contact with: oxidising agents,hydrobromic acid,iron.

Reacts violently developing heat on contact with: oxidising agents,hydrobromic acid,iron.

### 10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Pentactylenhexamine

Avoid exposure to: naked flames.do not smoking.

Build up of aerosols and fogs.

Benzyl alcohol

Avoid exposure to: heat.

### 10.5. Incompatible materials.

Pentactylenhexamine

Incompatible with: acids,oxidising agents,metals,chlorinated hydrocarbons.

Benzyl alcohol

Attacks various types of plastic materials.

### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Pentactylenhexamine

When heated to decomposition releases: nitrous gases.



Benzyl alcohol  
None dangerous decomposition products at normal use and storage conditions.

## SECTION 11. Toxicological information.

### 11.1. Information on toxicological effects.

#### ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:44,000 mg/l  
LC50 (Inhalation - mists / powders) of the mixture:Not classified (no significant component).  
LD50 (Oral) of the mixture:1598 mg/kg  
LD50 (Dermal) of the mixture:2293,333 mg/kg

Pentachylenhexamine  
LD50 (Oral).1591,4 mg/kg female rat  
LD50 (Dermal).1720 mg/kg male rabbit

Benzyl alcohol  
LD50 (Oral).1620 mg/kg male rat  
LD50 (Dermal).2000 mg/kg rabbit  
LC50 (Inhalation).> 4,178 mg/l/4h male/female rat

#### SKIN CORROSION / IRRITATION.

Corrosive for the skin.

#### SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye damage.

#### RESPIRATORY OR SKIN SENSITISATION.

Sensitising for the skin.

#### GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

#### CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

#### REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

#### STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

#### STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

#### ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

## SECTION 12. Ecological information.

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

### 12.1. Toxicity.

Pentachylenhexamine	
LC50 - for Fish.	180 mg/l/96h <i>Poecilia reticulata</i>
EC50 - for Crustacea.	17,5 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants.	0,7 mg/l/72h <i>Pseudokirchnerella subcapitata</i>
Chronic NOEC for Algae / Aquatic Plants.	0,25 mg/l <i>Pseudokirchnerella subcapitata</i>

**FB159 - REPIKIT 310 Comp. B**

Benzyl alcohol	
LC50 - for Fish.	460 mg/l/96h Pimephales promelas
EC50 - for Crustacea.	230 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants.	700 mg/l/72h Pseudokirchnerella subcapitata
Chronic NOEC for Crustacea.	51 mg/l Daphnia magna

**12.2. Persistence and degradability.**

Pentachylenehexamine	
Solubility in water.	very soluble > 500000 mg/l
NOT rapidly biodegradable.	

Benzyl alcohol	
Solubility in water.	very soluble 40000 mg/l
Rapidly biodegradable.	

95 - 97% 21d

**12.3. Bioaccumulative potential.**

Information not available.

**12.4. Mobility in soil.**

Pentachylenehexamine	
Partition coefficient: soil/water.	> 3,5

**12.5. Results of PBT and vPvB assessment.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects.**

Information not available.

**SECTION 13. Disposal considerations.**

**13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be

**FB159 - REPIKIT 310 Comp. B**

evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information.**

**14.1. UN number.**

ADR / RID, IMDG, 2735  
IATA:

**14.2. UN proper shipping name.**

ADR / RID: AMINES,  
LIQUID,  
CORROSIVE,  
N.O.S. or  
POLYAMINES,  
LIQUID,  
CORROSIVE,  
N.O.S.  
(pentaethylenehe  
xamine)  
IMDG: AMINES,  
LIQUID,  
CORROSIVE,  
N.O.S. or  
POLYAMINES,  
LIQUID,  
CORROSIVE,  
N.O.S.  
(pentaethylenehe  
xamine)  
IATA: AMINES,  
LIQUID,  
CORROSIVE,  
N.O.S. or  
POLYAMINES,  
LIQUID,  
CORROSIVE,  
N.O.S.  
(pentaethylenehe  
xamine)

**14.3. Transport hazard class(es).**

ADR / RID: Class: 8 Label: 8  
IMDG: Class: 8 Label: 8  
IATA: Class: 8 Label: 8



**14.4. Packing group.**

ADR / RID, IMDG, III  
IATA:

**14.5. Environmental hazards.**

ADR / RID: Environmentally  
Hazardous.



IMDG: Marine Pollutant.



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

**14.6. Special precautions for user.**

ADR / RID: HIN - Kemler: 80

Limited  
Quantities: 5  
L

Tunnel  
restriction  
code: (E)

Special Provision: -

IMDG: EMS: F-A, S-B

Limited  
Quantities: 5  
L

IATA: Cargo:

Maximum  
quantity: 60 L

Packaging  
instructions:  
856  
Packaging  
instructions:  
852

Pass.:

Maximum  
quantity: 5 L

Special Instructions:

A3, A803

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.**

Information not relevant.

**SECTION 15. Regulatory information.****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**

Seveso Category - Directive 2012/18/EC: E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product

Point. 3

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Skin Corr. 1C</b>	Skin corrosion, category 1C
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>Aquatic Chronic 4</b>	Hazardous to the aquatic environment, chronic toxicity, category 4
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H411</b>	Toxic to aquatic life with long lasting effects.



## FB159 - REPIKIT 310 Comp. B

- H412** Harmful to aquatic life with long lasting effects.
- H413** May cause long lasting harmful effects to aquatic life.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - ECHA website

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: all sections revised according to Regulation 830/2015/EC.